

ACTH-207 氯化橡胶沥青漆(管道专用)

ACTH-207 Chlorinated Rubber Asphalt Paint (For pipelines)

产品特性 Characteristics	极好的防腐性能和屏蔽性能、 Excellent anticorrosive and shielding property. 耐机械磨损性、干燥迅速、 Resistance to mechanical abrasion; fast drying. 良好的施工性能。 Good workability.					
产品用途	主要用于新船或旧船水线以下部位的防腐和埋地管道的外防腐。					
Uses	主要用了制加以印加小线以下部位的初熵和连地管理的外例熵。 As an antirust coating for the lower and upper part of waterline of new or existing ships, and for					
	exterior anticorrosion of underground pipelines.					
运 4	501					
颜 色 Color	黑色、棕色 Black or brown					
Coloi	Black of Glown					
施工条件	无气喷涂 Airless spray 推荐 Recommended					
Application method	喷嘴尺寸 Nozzle tip 0.8~0.9mm					
	压力 Fluid pressure 100~150kg/cm²					
	稀释比率 Thinning ratio 0~5%					
	适用于无气喷涂、空气喷涂、刷涂及辊涂。以辊涂为佳。					
	May be applied by spray, brush, or roller, and roller is preferred.					
稀释剂	专用稀释剂					
Thinner	Special thinner					
	*					
混合比率	单组分					
Mixing ratio	One-pack					
涂装膜厚	干膜: 50μm/道 湿膜: 85μm/道					
Film thickness	Dry film thickness:50μm /coat Wet film thickness:85μm /coat					
固体含量	54%					
Solid content						
比重	1.35					
Specific gravity	1.55					
Specific gravity						
涂 覆 率	理论值:0.13kg/m²/50μm L/m²/50μm					
Coverage rate	Theoretical: $0.13 \text{kg/m}^2/50 \mu \text{m}$ L/m ² /50 μm					
Č	实际值: 与表面处理, 外界环境, 施工方法等多种因素有关。					
	Actual: depending on the surface treatment, environment and application methods.					
干燥时间	温度 (℃) 10 20 30					
Drying time	Temperature ($^{\circ}$ C)					



	指触干燥 (min)	25	20	15			
	Dry to touch (min)						
	半硬干燥(hrs)	5.5	4	3.5			
	Dry hard (hrs)						
·	V C = E 1 (1)		4	2.5			
余装间隔 2	Min. 最小(hrs)	5.5	4	3.5			
Coating interval							
	Max. 最大 (hrs)						
储存期限	一年						
Shelf life	12 months						
 包 装 规 格	20kg/桶						
Packing specification	20 kg/barrel						
t defining specification	20 Mg 041101						
表面处理	底漆表面应清洁干燥、无污物。						
Surface preparation	The primer surfaces should be dry, clean and free of any contaminants.						
适用底材	裸钢或旧漆膜						
Substrate:	Bare steel or old paint film.						
安全注意事项	任何油漆施工中均应保证提供以下措施:						
Safety Precautions	The following be guaranteed during any paint applications: 避免接触皮肤和眼睛。						
	Avoid skin and eye contact.						
	如果油漆接触到皮肤或眼睛,应用大量水冲洗并立即就医。						
	In case of skin or eye contact, flush with large amount of water and immediately get medica						
	attention.						
	保证良好的通风。						
	Assure well-ventilated working place.						
	小心火灾或爆炸。						
	Take precautions of the risks of fire or explosion.						
	现场遵守一切健康安全规定。						
	Observe all health and safety regulations on site						
提醒注意	本说明书所提供信息均为目前我方所掌握最全面正确的资料,鉴于产品使用条件非我方所能控						
Declaration	制,此中信息不含担保,即仅在选取产品上对买方负责。由于我公司产品及生产工艺的不断发展,此中所有信息均以我方确认为准。						
	The information given on this technical data sheet is correct to the best of our knowledge. In						
	consideration of the application conditions of the product are beyond our control, so no guarantee is						
	involved herein, namely, we are responsible for the buyers only in terms of their selecting a product.						
	All data must be clarified from our company because of the constantly improvement of our product						
	and its manufacturing process.						